Declassified and Approved For Release 2012/09/13 : CIA-RDP78-03535A000500040006-5

Parts List IN-1

B	Battery, 22.5 volt Eveready 412E or Burgess U15
C_1	Capacitor, *.01 ufd silvered mica. Sprague type MS 11.
C_2	Capacitor, *0.1 ufd precision. Sprague "Styracon" type.
C_3 - 1" x 1.2" 30 VOLT TANTALUM, FANSTEEL STA 170	
J_1, J_2	Jack, Telex type 9220. DC.
R_1	Resistor, 51,000 ohm 5% ½ watt Allen Bradley
R_2	Resistor, variable wire-wound, 10 turn, 500,000 ohm Fairchild type 920
R_3	Resistor, variable wire-wound, 500 ohm Daystrom Pacific model 300-00
R_4	Resistor, variable composition with switch. Centralab Model 1 Radiohm.
S_1	Push Button, SPST Grayhill series no. 30
S_2	Switch, SPST ganged with R_4
S_3	SWITCH, SPDT HETHERINGTON TYPE T3103
T_1	Transformer, UTC Dot 4, 600 ohm to 3.2 ohm
Tr_1	Transistor, unijunction General Electric 4JX5A513 743 (ZJ14)
Tr_2	Transistor, NPN Sylvania type 2N35

* This is nominal value and may vary between units

This document is part of an integrated file. If separated from the file it must be subjected to individual systematic review.

Declassified and Approved For Release 2012/09/13 : CIA-RDP78-03535A000500040006-5